



General Information

All dimensions in mm
 General Tolerances: ±0.13mm
 Material: Chrome stainless steel AISI 420.
 Finish: Pickled and oiled.

Part number selection table

Associated Products

Example Part No:- **MSP - 1.5 - 6 - MCP**

Pin hub gears
 Shaft collars

Visit our online catalogue for associated products

Basic Part No.	Actual Dia ØD	Nom. Dia	Cham Dia ØB	Cham Length C	Recom. Hole Dia	Standard Lengths L	
MSP	0.85/0.91	0.8	0.75	0.30	0.80/0.84	4	5 6 8
	1.05/1.15	1.0	0.95	0.30	1.00/1.04	4	5 6 8 10 12
	1.62/1.73	1.5	1.40	0.50	1.50/1.60	5	6 8 10 12 14 16
	2.13/2.25	2.0	1.90	0.70	1.99/2.10	6	8 10 12 14 16 18
	2.65/2.78	2.5	2.40	0.70	2.49/2.60		10 12 14 16 18
	3.15/3.30	3.0	2.90	0.90	2.99/3.10		14 16 18 20

- Coiled steel pin for location and alignment.
- Suitable for locating Reliance’s gears on ground shaft for lower torque or less demanding applications.
- Large hole diameter tolerance.

Non-standard options, please enquire....

- Imperial sizes.
- Alternative materials.

www.rpmechatronics.co.uk